

关于 [i](#)

数据类型 SUM, GROUP ORDER
数据类型。

数据类型 (20,19,18...1) Player
数据类型。

数据类型:

```
CREATE TABLE `tbl_event_A` (  
  `sn` int(11) unsigned NOT NULL AUTO_INCREMENT COMMENT 'SN',  
  `playerid` int(11) unsigned NOT NULL COMMENT 'PlayerID',  
  `logday` int(11) unsigned NOT NULL COMMENT '日期',  
  `winpoint` int(11) NOT NULL COMMENT '胜利点数',  
  `score` int(11) NOT NULL COMMENT '得分',  
  `week` tinyint(3) NOT NULL COMMENT '周',  
  PRIMARY KEY (`sn`),  
  KEY `logdate` (`logday`)  
) ENGINE=MyISAM; Query Select  
数据类型。
```

[select 数据类型](#) " 数据类型。
MS SQL RANK() OVER() ROW_NUMBER() 数据类型
MySQL [mysql select auto increment number](#) 数据类型。
数据类型。

MySQL (数据类型) 数据类型

[] [MySQL] SELECT

Administrator
2014 18:53

```
SELECT @s:=@s+1 serial_number, student_id, student_name, student_avg
FROM students, (SELECT @s:= 0) AS s
WHERE student_avg > 4;
```

query

```
SELECT @SN:=@SN+1 as Score, PlayerID, SUM(winpoint) as WinPoint FROM
tbl_dailyplayerpoint,(SELECT @SN:=0) as Dummy WHERE logday='$Yesterday' GROUP BY
PlayerID ORDER BY WinPoint DESC LIMIT 20;
```

query SUM, GROUP ORDER BY

Table with 4 columns: Score, PlayerID, WinPoint, and an unnamed column. Data rows include values like 4, 20441389, 60, 31, 12158264, 35, 10, 11551464, 41, 23, etc.

GROUP @SN:=@SN+1 query @SN:=@SN+1 @SN GROUP

```
SELECT 21-(@SN:=@SN+1) as Score, PlayerID, WinPoint FROM (SELECT PlayerID,
SUM(winpoint) as WinPoint FROM tbl_dailyplayerpoint WHERE logday='$Yesterday' GROUP
BY PlayerID ORDER BY WinPoint DESC LIMIT 20) as Dummy1, (SELECT @SN:=0) as
Dummy2;
```

Table with 4 columns: Score, PlayerID, WinPoint, and an unnamed column. Data rows include values like 20, 4, 20441389, 19, 31, 12158264, 18, etc.

query

```
INSERT INTO tbl_event_A (score,playerid,winpoint,logday,week) SELECT
```

[] [MySQL] SELECT

Administrator
20 2014 18:53 -

21-(@SN:=@SN+1), PlayerID, WinPoint, '\$Yesterday', '\$week' FROM (SELECT PlayerID, SUM(winpoint) as WinPoint FROM tbl_dailyplayerpoint WHERE logday='\$Yesterday' GROUP BY PlayerID ORDER BY WinPoint DESC LIMIT 20) as Dummy1, (SELECT @SN:=0) as Dummy2;

PHP cron table !!
!!